



Description: LIMA starter set: 2 end post, beam set

Item number: DFDH-R-2E

GTIN: 4250912314047

Customs tariff number: 39269097

Material: Polyethylene

Width (mm): 1755
Height (mm): 1200
Depth/Length (mm): 225
Installation width (mm): 1755

Colour: yellow - black

Foot plate width (mm): 225

Foot plate depth (mm): 225

Foot plate height (mm): 10

Foot plate colour: black

Area of application: indoor and outdoor use

Mounting: bolting

Delivery is: disassembled

Number of mounting holes: 8

Fixing included: Concrete screw anchors M12 x 80 mm

Tested to withstand force (Joule): IMPACT ZONE 1: 90° 4.000 J

IMPACT ZONE 2: 90° 15.000 J 67,5° 17.600 J 45° 30.000 J 22,5° 102.700 J

IMPACT ZONE 3: 90° 4.000 J

Vehicle: Heavy Duty LPG forklifts

Vehicle weight equivalent (kg):11.590 kgVehicle equivalent speed (km/h):3,0 km/h

Tested according to: PAS 13: 2017 chap. 7/7.8

Deformation under maximal force (mm): 250

Chemical Resistance: high-ISO/TR 10358

Temperature Range: -40° bis +50°

Recyclability: 100%
Warranty: 5 years
Brand: d-flexx

Contain: 2x DFDH-M-E; 1x DFDH-M-H1







Description: d-flexx Lima barrier end post

Item number: DFDH-M-E

GTIN: 4250912395220

Customs tariff number: 39269097

Material: Polyethylene

Width (mm): 619

Height (mm): 1200

Depth/Length (mm): 225

Installation width (mm):

Net weight (kg): 20,23

Width without foot plate (mm): 619

Depth without foot plate (mm): 200

Colour: yellow - black

Foot plate width (mm): 225

Foot plate depth (mm): 225

Foot plate height (mm): 10

Foot plate colour: black

Area of application: indoor and outdoor use

Mounting: bolting

Delivery is: partly disassembled

Number of mounting holes: 4

Fixing included: Concrete screw anchors M12 x 80 mm

174

Tested to withstand force (Joule): IMPACT ZONE 1: 90° 4.000 J

Vehicle: Heavy Duty LPG forklifts

Vehicle weight equivalent (kg): 11.590 kg
Vehicle equivalent speed (km/h): 3,0 km/h

Tested according to: PAS 13: 2017 chap. 7/7.8

Inclination angle: 15°

Chemical Resistance: high-ISO/TR 10358

Temperature Range: -40° bis +50°

Recyclability: 100%

Warranty: 5 years

Brand: d-flexx



