



<b>Description:</b>	DELTA 1200/3 starter set: 2 end post, beam set
<b>Item number:</b>	DFFS3-H-2E
<b>GTIN:</b>	4250912314009
<b>Customs tariff number:</b>	39269097
<b>Material:</b>	Polyethylene
<b>Width (mm):</b>	1680
<b>Height (mm):</b>	1200
<b>Depth/Length (mm):</b>	150
<b>Installation width (mm):</b>	1680
<b>Colour:</b>	yellow - black
<b>Foot plate width (mm):</b>	150
<b>Foot plate depth (mm):</b>	150
<b>Foot plate height (mm):</b>	10
<b>Foot plate colour:</b>	black
<b>Area of application:</b>	indoor and outdoor use
<b>Mounting:</b>	dowel and screw on
<b>Delivery is:</b>	disassembled
<b>Number of mounting holes:</b>	8
<b>Fixing included:</b>	Concrete screw anchors M10 x 70 mm
<b>Tested to withstand force (Joule):</b>	IMPACT ZONE 1: 90° 2.500 J IMPACT ZONE 2: 90° 3.000 J 67,5° 3.500 J 45° 6.000 J 22,5° 20.500 J IMPACT ZONE 3: 90° 2.500 J
<b>Vehicle:</b>	Low Lift pallet truck
<b>Vehicle weight equivalent (kg):</b>	3.150 kg
<b>Vehicle equivalent speed (km/h):</b>	5,0 km/h
<b>Tested according to:</b>	PAS 13: 2017 chap. 7/7.8
<b>Deformation under maximal force (mm):</b>	250
<b>Chemical Resistance:</b>	high-ISO/TR 10358
<b>Temperature Range:</b>	-40° bis +50°
<b>Recyclability:</b>	100%
<b>Warranty:</b>	5 years
<b>Brand:</b>	d-flexx
<b>Contain:</b>	2x DFFS-M-E 1x DFFS-H1

