



<b>Description:</b>	ECHO starter set: 2 end post, beam set
<b>Item number:</b>	DFVB+R-2E
<b>GTIN:</b>	4250912314023
<b>Customs tariff number:</b>	39269097
<b>Material:</b>	Polyethylene
<b>Width (mm):</b>	1755
<b>Height (mm):</b>	1200
<b>Depth/Length (mm):</b>	225
<b>Installation width (mm):</b>	1755
<b>Colour:</b>	yellow - black
<b>Foot plate width (mm):</b>	225
<b>Foot plate depth (mm):</b>	225
<b>Foot plate height (mm):</b>	10
<b>Foot plate colour:</b>	black
<b>Area of application:</b>	indoor and outdoor use
<b>Mounting:</b>	bolting
<b>Delivery is:</b>	partly disassembled
<b>Number of mounting holes:</b>	8
<b>Fixing included:</b>	Concrete screw anchors M12 x 80 mm
<b>Tested to withstand force (Joule):</b>	IMPACT ZONE 1: 90° 4.000 J IMPACT ZONE 2: 90° 9.000 J 67,5° 10.500 J 45° 18.000 J 22,5° 61.500 J IMPACT ZONE 3: 90° 4.000 J
<b>Vehicle:</b>	LPG forklift
<b>Vehicle weight equivalent (kg):</b>	4.320 kg
<b>Vehicle equivalent speed (km/h):</b>	4,9 km/h
<b>Tested according to:</b>	PAS 13: 2017 chap. 7/7.8
<b>Deformation under maximal force (mm):</b>	250
<b>Chemical Resistance:</b>	high-ISO/TR 10358
<b>Temperature Range:</b>	-40° bis +50°
<b>Recyclability:</b>	100%
<b>Warranty:</b>	5 years
<b>Brand:</b>	d-flexx
<b>Contain:</b>	2x DFVB+E; 1x DFVB+H1





<b>Description:</b>	traffic barrier X Echo end post
<b>Item number:</b>	DFVB+E
<b>GTIN:</b>	4250912311244
<b>Customs tariff number:</b>	39269097
<b>Material:</b>	Polyethylene
<b>Width (mm):</b>	619
<b>Height (mm):</b>	1200
<b>Depth/Length (mm):</b>	225
<b>Installation width (mm):</b>	174
<b>Net weight (kg):</b>	16,91
<b>Depth without foot plate (mm):</b>	200
<b>Colour:</b>	yellow - black
<b>Foot plate width (mm):</b>	225
<b>Foot plate depth (mm):</b>	225
<b>Foot plate height (mm):</b>	10
<b>Area of application:</b>	indoor and outdoor use
<b>Mounting:</b>	bolting
<b>Delivery is:</b>	partly disassembled
<b>Number of mounting holes:</b>	4
<b>Fixing included:</b>	Concrete screw anchors M12 x 80 mm
<b>Tested to withstand force (Joule):</b>	IMPACT ZONE 1: 90° 4.000 J
<b>Vehicle:</b>	LPG forklift
<b>Vehicle weight equivalent (kg):</b>	4.320 kg
<b>Vehicle equivalent speed (km/h):</b>	4,9 km/h
<b>Tested according to:</b>	PAS 13: 2017 chap. 7/7.8
<b>Inclination angle:</b>	15°
<b>Chemical Resistance:</b>	high-ISO/TR 10358
<b>Temperature Range:</b>	-40° bis +50°
<b>Recyclability:</b>	100%
<b>Warranty:</b>	5 years
<b>Brand:</b>	d-flexx

